

STUD BOY APPLICATION CHART

ARCTIC CAT 1998

Snowmobile Information			Riding Style				Wearbars		
			Safety		Performance				
1998 Model	Lug Height	Track Length	Stud Length	Stud Quantity	Stud Length	Stud Quantity	Deuce	Round	Shaper
Bearcat 340	0.750	15x136	0.875	81	0.875	108	NA	CAT-R2077-(add size)	NA
Bearcat 440	0.750	15x136	0.875	81	0.875	108	NA	CAT-R2077-(add size)	NA
Bearcat 550	0.900	20x156	1.000	93	1.000	124	NA	CAT-R2077-(add size)	NA
Cougar	0.750	15x121	0.875	72/96	0.875	96/120	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Cougar DLX	0.750	15x121	0.875	72/96	0.875	96/120	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Cougar MC	0.920	15x136	1.000	81	1.0/1.01	108/135	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
EXT 580 EFI	0.750	15x121	0.875	96	1.000	120/144	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
EXT 580 DLX	0.750	15x121	0.875	96	1.000	120/144	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
EXT 600 Touring	0.750	15x121	0.875	120	1.000	144/168	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
EXT 600 Triple	0.750	15x121	0.875	120	1.000	144/168	NA	CAT-R2077-(add size)	NA
Jag 340/440/DLX	0.750	15x121	0.875	72	0.875	72/96	NA	CAT-R2077-(add size)	NA
Pantera 580	0.750	15x136	0.875	81	0.875	108/135	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Pantera 800	0.750	15x136	0.875	135	0.875	162	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Panther 440	0.750	15x136	0.875	81	0.875	108	NA	CAT-R2077-(add size)	NA
Panther 550	0.750	15x136	0.875	108	0.875	108/135	NA	CAT-R2077-(add size)	NA
Powder Extreme	2.000	15x136	NA	NA	NA	NA	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Powder Special	2.000	15x136	NA	NA	NA	NA	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Thundercat	0.850	15x121	1.000	144/168	1.080	192/240	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Thundercat MC	2.000	15x136	NA	NA	NA	NA	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
Z 440	0.750	15x121	0.875	72/96	1.000	96/120	NA	CAT-R2076-(add size)	NA
ZL 440	0.750	15x121	0.875	72/96	1.000	96/120	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
ZL 500	7.500	15x121	0.875	96	1.000	120/144	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
ZR 440/500	0.850	15x121	1.000	96	1.0/1.08	120/144	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
ZR 600/600EFI	0.850	15x121	1.000	96/120	1.0/1.08	120/144	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
ZRT 600	0.850	15x121	1.000	120/144	1.0/1.08	192	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)
ZRT 800	0.850	15x121	1.000	144/168	1.0/1.08	240	CAT-D2093-(add size)	CAT-R2093-(add size)	CAT-S2093-(add size)

*121" Tracks Have 48 Lugs /128" Tracks Have 51 Lugs/ 136" Tracks Have 54 Lugs / 141" Tracks Have 47 Lugs/144" Tracks Have 57 Lugs /156" Tracks Have 62 Lugs

**** PLEASE REMEMBER THAT "DEUCE" BARS ARE SOLD AS SINGLE BARS – NOT AS A PAIR**

Liberty Products, Inc. recommends that tunnel and/or heat exchanger protection be installed in all snowmobiles when traction products are utilized. Even if your snowmobile is equipped with factory tunnel protection we suggest that you check for adequate clearance of traction products before you ride. Riding without performing a clearance check can result in serious damage to your snowmobile. Stud quantity and carbide length must be balanced for safe and proper handling. If you